

KARYA DijİTAL

HIGH PERFORMANCE SOLUTIONS

M6

- 243 m²/h printing speed
- 190 cm maximum printing width
- Outstanding price/performance ratio for its Epson i3200 heads
- n.6 printheads
- Very precise printing, perfectly clear output
- Robust Structure

Printing Speed

243 m²/h



Printing Width

190 cm
width



TRU JET

TRU PAPER

J TECH

K//AN
DIGITAL

ergosoft
rip solutions

İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.
No: 22, Merter - Güngören / İSTANBUL
T +90 212 637 03 34 | F +90 212 637 03 38

BURSA

Anadolu Mh. Karlıdağ Sk. No: 37
Yıldırım - BURSA
T +90 224 364 61 40 | F +90 224 364 61 46

www.karyadijital.com
satis@karyadijital.com

[f](#) [t](#) [@](#) [v](#) [in](#) /karyadijital



- Mimimum drop size 2 pl
- n.6 staggered Epson i3200 printhead
- n.3200 nozzles per head, n.19200 nozzles in total

- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean




- Pneumatic shafts are used for paper feeding & take-up, which can support 1000 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding

- Independent pump for each print head group
- Independent cleaning pump for wiper & flashing stage.



- Continuous pinch roller design to prevent uneven paper.
- Patented paper suction system with diagonal channels

- Special design patented 2 stage ink feeding system



TECHICAL PROPERTIES

Print Head	n.6 On demand Piezo print head / Staggered
Maximum Print Width	1900 mm
Ink Type	CMYK, Dye Sublimation
Number of Colors	4 Colors, 6-8 Colors (Optional)
Ink Feeding System	* 2.5 lt / color opened ink feeding system (filter system) * 11 lt / color Jumbo ink system (filter, sub-tank, level & error sensor) (optional)
Media	Width: 210 ~ 1910 mm Thickness: 1 mm or less Weight: up to 75 kg Length: 500 - 1000 m Roll Diameter: 50 mm - 75 mm
Printing Speeds	360 x 1200 dpi - 2 pass 243 m ² /h 360 x 1800 dpi - 3 pass 182 m ² /h 720 x 1200 dpi - 4 pass 122 m ² /h
RIP Software	ErgoRIP (textprint) / Neostampa / Maintop
Interface	Gigabit Ethernet
Power Features	AC 100 ~ 120 V ± 10 / AC 220 ~ 240 V ± 10, 50/60 Hz + 1Hz
Power Consumption	300 W or less (except drying unit)
Net Sizes (G x D x Y)	3550 x 950 x 1950mm (G x D x Y)
Gross Sizes (G x D x Y)	3550 x 1700 x 1950mm (G x D x Y)
Net / Gross Weight	600 kg / 755 kg