

HIGH PERFORMANCE SOLUTIONS



- 540 m²/h printing speed
- 190 cm maximum printing width
- **Outstanding price/performance ratio** for its epson i3200 heads
- n.12 printheads
- Very precise printing, perfectly clear output
- **Robust Structure**

Printing Speed



Printing Width





















- Minimum drop size 2 pl
- n.12 epson i3200 printhead
- n. 3200 nozzles per head,
 n. 38.400 nozzles in total



- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean.



- Pneumatic shafts are used for paper feeding & take-up, which can support 3000 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding



- Independent pump for each print head.
- Independent cleaning pump for wiper & flashing stage



- Continuous pinch roller design to prevent uneven paper
- Patented paper suction system with diagonal channels



Special design patented2 stage ink feeding system

TECHNICAL PROPERTIES

Print Head	n.12 Epson i3200 on-demand Piezo
Maximum Print Width	1900mm
Ink Type	Sublimation Dispers Ink, Graphic pigment Ink
Number of Colors	4 colors, 6 colors, 8 colors (Optional) SCAN FOR PACKING DETAILS
Ink Feeding System	25L Electronic Supply
Media	Weight: up to 145 kg
	Lenght: 2000 – 3000 mm
	Roll Diameter: 50 mm – 75 mm
Printing Speeds	360 x 1200 – 1 pass 540 m²/h
	720 x 1200 – 2 pass 270m²/h
RIP Software	ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera
Power Consumption	Printer: 1,5kW; Heater 4,8kW*2; Total 15kW
Net Dimensions (LxWxH)	3490x1900x2800 mm