

## **HIGH PERFORMANCE SOLUTIONS**



- 700 m<sup>2</sup>/h printing speed
- 190 cm maximum printing width
- Outstanding price/performance ratio for its epson i3200 heads
- n.16 printheads
- Very precise printing, perfectly clear output
- **Robust Structure**













## **İSTANBUL**

Mehmet Nesih Özmen Mh. Savur Sk. No: 22 Merter – Güngören / İstanbul – Turkey P +90 212 637 03 34

## **BURSA** Panayır Mahallesi 3. Pınar Caddesi No:265 Osmangazi- Bursa - Turkey P +90 224 211 45 79

www.karyadijital.com sales@karyadijital.com (f) () () () (in) /karyadijital



- Minimum drop size 2 pl
- n.16 epson i3200 printhead
- n. 3200 nozzles per head,
  n. 51200 nozzles in total



- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean.




- Pneumatic shafts are used for paper feeding & take-up, which can support 10000 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding



- Independent pump for each print head.
- Independent cleaning pump for wiper & flashing stage



- Continuous pinch roller design to prevent uneven paper
- Patented paper suction system with diagonal channels



- Special design patented 2 stage ink feeding system

TECHNICAL PROPERTIES		
Print Head	n.16 Epson i3200 on-demand Piezo	■縦■
Maximum Print Width	1900mm	
Ink Type	Sublimation Dispers Ink, Graphic pigment Ink	
Number of Colors	4 colors, 8 colors (Optional)	SCAN FOR PACKING DETAILS
Ink Feeding System	25L Electronic Supply	
Media	Weight: up to 145 kg	
	Lenght: 300 – 100 mm	
	Roll Diameter: 50 mm – 75 mm	
Printing Speeds	360 x 1200 – 1 pass 700 m²/h	
	720 x 1200 – 2 pass 350m²/h	
RIP Software	ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera	
Power Consumption	Total: 16,7 kW	
Net Dimensions (LxWxH)	4310x2050x2310 mm	