

## **HIGH PERFORMANCE SOLUTIONS**



- 75 m<sup>2</sup>/h printing speed
- 190 cm maximum printing width
- **Outstanding price/performance ratio** for its epson i3200 heads
- n.2 printheads
- Very precise printing, perfectly clear output
- **Robust Structure**

## **Printing Speed**



## **Printing Width**





















- Mimimum drop size 2 pl
- n.2 staggered epson i3200 printhead
- n. 3200 nozzles per head,
  n. 6400 nozzles in total.



- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean.



 From suction system to dampers, filtration system to electronics, many innovative approach & relative patents.



- Independent pump for each print head.
- Independent cleaning pump for wiper & flashing stage.



- Continuous pinch roller design to prevent uneven paper.
- Patented paper suction system with diagonal channels.



Special design patented
2 stage ink feeding system.

## **TECHNICAL PROPERTIES**

TECHNICAL PROPERTIES	
Print Head	n.2 on-demand Piezo / staggered
Maximum Print Width	1900mm
Ink Type	Sublimation Dispers Ink, Graphic pigment Ink
Number of Colors	4 colors, 8 colors (Optional)  SCAN FOR PACKING DETAILS
Ink Feeding System	Open bulk system with 20 µm filter
	Weight: up to 20 kg
Media	Lenght: 200 – 300 mm
	Roll Diameter: 50 mm – 75 mm
	360 x 1200 - 2 pass 75 m²/h
Printing Speeds	360 x 1800 - 3 pass 56 m²/h
	720 x 1200 – 4 pass 38 m²/h
RIP Software	ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera
Power Consumption	300 W or less (except drying unit)
Net Dimensions (LxWxH)	3130x850x1950 mm