

## HIGH PERFORMANCE SOLUTIONS

# M6

- 243 m<sup>2</sup>/h printing speed
- 190 cm maximum printing width
- Outstanding price/performance ratio for its Epson i3200 heads
- n.6 printheads
- Very precise printing, perfectly clear output
- Robust Structure

Printing Speed

**243** m<sup>2</sup>/sa

Printing Width

**190** cm  
up to



KARYA Dijital

**K//AN**  
DIGITAL

**J**  
TECH

*inēdit*

**CALDERA**  
WIDE FORMAT IMAGING

**ergosoft**  
rip solutions

İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.  
No: 22 Merter - Güngören / İstanbul - Turkey  
P +90 212 637 03 34

BURSA

Panayır Mahallesi 3. Pınar Caddesi No:265  
Osmangazi- Bursa - Turkey  
P +90 224 211 45 79

[www.karyadijital.com](http://www.karyadijital.com)

[sales@karyadijital.com](mailto:sales@karyadijital.com)

[f](#) [t](#) [@](#) [v](#) [in](#) /karyadijital



- Minimum drop size 2 pl
- n.6 staggered epson i3200 printhead
- n. 3200 nozzles per head, n. 19200 nozzles in total



- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean.




- Pneumatic shafts are used for paper feeding & take-up, which can support 1000 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding



- Independent pump for each print head.
- Independent cleaning pump for wiper & flashing stage




- Continuous pinch roller design to prevent uneven paper
- Patented paper suction system with diagonal channels



- Special design patented 2 stage ink feeding system

## TECHNICAL PROPERTIES

Print Head	n.6 on-demand Piezo / staggered	 <p>SCAN FOR PACKING DETAILS</p>
Maximum Print Width	1900mm	
Ink Type	Sublimation Dispers Ink, Graphic pigment Ink	
Number of Colors	4 colors, 6 colors, 8 colors (Optional)	
Ink Feeding System	* 2.5 lt/color opened ink feeding system (filter system). * 11 lt/color Jumbo ink system (filter, sub-tank, level & errorsensor)(optional).	
Media	Weight: up to 75 kg Lenght: 500 - 1000 mm Roll Diameter: 50 mm - 75 mm	
Printing Speeds	360 x 1200 - 2 pass 243 m <sup>2</sup> /h 360 x 1800 - 3 pass 182 m <sup>2</sup> /h 720 x 1200 - 4 pass 122 m <sup>2</sup> /h	
RIP Software	ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera	
Power Consumption	300 W or less (except drying unit)	
Net Dimensions (LxWxH)	3490x1900x2800 mm	