

HIGH PERFORMANCE SOLUTIONS

M6

- 243 m²/h printing speed
- 190 cm maximum printing width
- Outstanding price/performance ratio for its Epson i3200 heads
- n.6 printheads
- Very precise printing, perfectly clear output
- Robust Structure

Printing Speed

243 m²/h



Printing Width

190 cm
up to



KARYA Dijital

K//AN
DIGITAL



inēdit

CALDERA
WIDE FORMAT IMAGING

 **ergosoft**
rip solutions

İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.
No: 22 Merter - Güngören / İstanbul - Turkey
P +90 212 637 03 34

BURSA

Panayır Mahallesi 3. Pınar Caddesi No:265
Osmangazi- Bursa - Turkey
P +90 224 211 45 79

www.karyadijital.com

sales@karyadijital.com

     /karyadijital



- Minimum drop size 2 pl
- n.6 staggered Epson i3200 printhead
- n. 3200 nozzles per head, n. 19200 nozzles in total



- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean.




- Pneumatic shafts are used for paper feeding & take-up, which can support 1000 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding



- Independent pump for each print head.
- Independent cleaning pump for wiper & flashing stage



- Continuous pinch roller design to prevent uneven paper
- Patented paper suction system with diagonal channels



- Special design patented 2 stage ink feeding system

TECHNICAL PROPERTIES

| | | |
|------------------------|--|--|
| Print Head | n.6 on-demand Piezo / staggered |  SCAN FOR PACKING DETAILS |
| Maximum Print Width | 1900mm | |
| Ink Type | Sublimation Dispers Ink, Graphic pigment Ink | |
| Number of Colors | 4 colors, 6 colors, 8 colors (Optional) | |
| Ink Feeding System | * 2.5 lt/color opened ink feeding system (filter system). * 11 lt/color Jumbo ink system (filter, sub-tank, level & errorsensor)(optional). | |
| Media | Weight: up to 75 kg Lenght: 500 - 1000 mm Roll Diameter: 50 mm – 75 mm | |
| Printing Speeds | 360 x 1200 – 2 pass 243 m²/h 360 x 1800 – 3 pass 182 m²/h 720 x 1200 – 4 pass 122 m²/h | |
| RIP Software | ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera | |
| Power Consumption | 300 W or less (except drying unit) | |
| Net Dimensions (LxWxH) | 3490x1900x2800 mm | |