

## **HIGH PERFORMANCE SOLUTIONS**



- 216 m<sup>2</sup>/h printing speed
- 260 cm maximum printing width
- **Outstanding price/performance ratio** for its epson i3200 heads
- n.4 printheads
- Very precise printing, perfectly clear output
- **Robust Structure**









up ta












## **İSTANBUL**

Mehmet Nesih Özmen Mh. Savur Sk. No: 22 Merter – Güngören / İstanbul – Turkey P +90 212 637 03 34

## **BURSA** Panayır Mahallesi 3. Pınar Caddesi No:265 Osmangazi- Bursa - Turkey P +90 224 211 45 79


www.karyadijital.com sales@karyadijital.com (f) () () () (in) /karyadijital



- Mimimum drop size 2 pl
- n.4 staggered epson i3200 printhead
- n. 3200 nozzles per head, n. 12800 nozzles in total



- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean.



- Pneumatic shafts are used for paper feeding & take-up, which can support 500 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding



- Independent pump for each print head.
- Independent cleaning pump for wiper & flashing stage



- Continuous pinch roller design to prevent uneven paper
- Patented paper suction system with diagonal channels



- Special design patented 2 stage ink feeding system

TECHNICAL PROPERTIES	
Print Head	n.4 on-demand Piezo / staggered
Maximum Print Width	2600mm
Ink Type	Sublimation Dispers Ink, Graphic pigment Ink
Number of Colors	4 colors, 6 colors, 8 colors (Optional) SCAN FOR PACKING DETAILS
Ink Feeding System	Open bulk system with 20 µm filter
	Weight: up to 200 kg
Media	Lenght: 400 – 800 mm
	Roll Diameter: 50 mm – 75 mm
	360 x 1200 – 2 pass 215 m²/h
Printing Speeds	360 x 1800 – 3 pass 160 m²/h
	720 x 1200 – 4 pass 110 m²/h
RIP Software	ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera
Power Consumption	300 W or less (except drying unit)
Net Dimensions (LxWxH)	4400x1900x2250 mm