

HIGH PERFORMANCE SOLUTIONS

M4³²

- 225 m²/h printing speed
- 320 cm maximum printing width
- Outstanding price/performance ratio for its Epson i3200 heads
- n.4 printheads
- Very precise printing, perfectly clear output
- Robust Structure



Printing Speed

225 m²/h

Printing Width

320 cm
up to



KARYA Dijital

K//AN
DIGITAL

J
TECK

inēdit

CALDERA
WIDE FORMAT IMAGING

ergosoft
rip solutions

İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.
No: 22 Merter - Güngören / İstanbul - Turkey
P +90 212 637 03 34

BURSA

Panayır Mahallesi 3. Pınar Caddesi No:265
Osmangazi- Bursa - Turkey
P +90 224 211 45 79

www.karyadijital.com

sales@karyadijital.com

[f](#) [t](#) [@](#) [v](#) [in](#) /karyadijital



- Mimimum drop size 2 pl
- n.4 staggered epson i3200 printhead
- n. 3200 nozzles per head, n. 12800 nozzles in total



- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean.




- Pneumatic shafts are used for paper feeding & take-up, which can support 500 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding



- Independent pump for each print head.
- Independent cleaning pump for wiper & flashing stage



- Continuous pinch roller design to prevent uneven paper
- Patented paper suction system with diagonal channels



- Special design patented 2 stage ink feeding system

TECHNICAL PROPERTIES

Print Head	n.4 on-demand Piezo / staggered	 SCAN FOR PACKING DETAILS
Maximum Print Width	3200mm	
Ink Type	Sublimation Dispers Ink, Graphic pigment Ink	
Number of Colors	4 colors, 6 colors, 8 colors (Optional)	
Ink Feeding System	Open bulk system with 20 µm filter	
Media	Weight: up to 200 kg Lenght: 400 - 800 mm Roll Diameter: 50 mm - 75 mm	
Printing Speeds	360 x 1200 - 2 pass 225 m ² /h 360 x 1800 - 3 pass 170 m ² /h 720 x 1200 - 4 pass 115 m ² /h	
RIP Software	ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera	
Power Consumption	300 W or less (except drying unit)	
Net Dimensions (LxWxH)	4950x1900x2250 mm	