

HIGH PERFORMANCE SOLUTIONS



- 387 m²/h printing speed
- 320 cm maximum printing width
- Outstanding price/performance ratio for its epson i3200 heads
- · n.8 printheads
- · Very precise printing, perfectly clear output
- · Robust Structure

Printing Speed



Printing Width





















- Minimum drop size 2 pl
- n.8 epson i3200 printhead
- n. 3200 nozzles per head, n. 25.600 nozzles in total




- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean.



- Pneumatic shafts are used for paper feeding & take-up, which can support 500 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding



- Independent pump for each print head.
- Independent cleaning pump for wiper & flashing stage



- Continuous pinch roller design to prevent uneven paper
- Patented paper suction system with diagonal channels



Special design patented2 stage ink feeding system

TECHNICAL PROPERTIES

Print Head	n.8 i3200 on-demand Piezo / staggered	回経回	
Maximum Print Width	3200mm	TOTAL SAN	
Ink Type	Sublimation Dispers Ink, Graphic pigment Ink		
Number of Colors	4 colors, 8 colors (Optional)	SCAN FOR PACKING DETAILS	
	* 5 lt/color opened ink feeding system (filter systen	ng system (filter system).	
Ink Feeding System	* 11 lt/color Jumbo ink system (filter, sub-tank, level &		
	errorsensor)(optional).		
Media	Weight: up to 200 kg		
	Lenght: 400 – 500 mm		
	Roll Diameter: 300 mm		
Printing Speeds	360 x 1200 - 1 pass 387 m²/h		
	720 x 1200 - 2 pass 194 m²/h		
RIP Software	ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera		
Power Consumption	300 W or less (except drying unit)		
Net Dimensions (LxWxH)	4950x1900x2250 mm		