

HIGH PERFORMANCE SOLUTIONS

- 360 m²/h printing speed
- 190 cm maximum printing width
- Outstanding price/performance ratio for its epson i3200 heads
- n.8 printheads
- Very precise printing, perfectly clear output
- Robust Structure



İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk. No: 22 Merter – Güngören / İstanbul – Turkey P +90 212 637 03 34

BURSA Panayır Mahallesi 3. Pınar Caddesi No:265 Osmangazi- Bursa - Turkey P +90 224 211 45 79

www.karyadijital.com sales@karyadijital.com (f) () (a) (a) (karyadijital)

Printing Speed



- Minimum drop size 2 pl

- n.8 epson i3200 printhead
- n. 3200 nozzles per head,
 n. 25.600 nozzles in total



- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean.




- Pneumatic shafts are used for paper feeding & take-up, which can support 500 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding



- Independent pump for each print head.
- Independent cleaning pump for wiper & flashing stage



- Continuous pinch roller design to prevent uneven paper
- Patented paper suction system with diagonal channels



Special design patented
 2 stage ink feeding system

TECHNICAL PROPERTIES

Print Head	n.8 i3200 on-demand Piezo / staggered	■揺■
Maximum Print Width	1900mm	
Ink Type	Sublimation Dispers Ink, Graphic pigment Ink	
Number of Colors	4 colors, 8 colors (Optional)	SCAN FOR PACKING DETAILS
	* 2.5 lt/color opened ink feeding system (filter system).	
Ink Feeding System	* 11 lt/color Jumbo ink system (filter, sub-tank, level &	
	errorsensor)(optional).	
Media	Weight: up to 75 kg	
	Lenght: 2000 – 3000 mm	
	Roll Diameter: 50 mm – 75 mm	
Printing Speeds	360 x 1200 – 1 pass 360 m²/h	
	720 x 1200 – 2 pass 180 m²/h	
	ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera	
RIP Software		
Power Consumption	300 W or less (except drying unit)	
Net Dimensions (LxWxH)	3490x1900x2500 mm	