

## SUBLIMATION PAPER PRINTING

# G30

- 1200 m<sup>2</sup>/h printing speed
- 190 cm maximum printing width
- Outstanding price/performance ratio for its Epson i3200 heads
- 30 printheads
- Very precise printing, perfectly clear output
- Robust Structure

Max. Roll Weight

**800 kg**



Printing Speed

**1200 m<sup>2</sup>/h**



Printing Width

**190 cm**  
up to



KARYA Dijital

K//AN  
DIGITAL

TECK

inēdit

CALDERA  
WIDE FORMAT IMAGING

ergosoft  
rip solutions

İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.  
No: 22 Merter - Güngören / İstanbul - Turkey  
P +90 212 637 03 34

BURSA

Panayır Mahallesi 3. Pınar Caddesi No:265  
Osmangazi- Bursa - Turkey  
P +90 224 211 45 79

[www.karyadijital.com](http://www.karyadijital.com)

[sales@karyadijital.com](mailto:sales@karyadijital.com)

[f](#) [t](#) [i](#) [v](#) [in](#) /karyadijital




- Steel beam & rail longer life and more stable
- Linear motor higher print speed



- Robust Structure
- 15,000m jumbo system



- Excellent printing precision
- Outstanding performance



- PLC intelligent feeder and take-up motion control system
- Smoother movement, steadier paper take-up



- Independent cleaning station for each head
- Longitudinal Ink Squeegee better protect of printhead
- Independent pump for each print head



- Revolutionary hot air circulation system 30%~40% energy saving
- Uniform drying effect, improved paper stability and pattern
- Excellent paper take-up effect and transfer results.




- Patented ink supply system including serial connected damper structure.
- Improved standby and re-printing performance of the printheads.
- More convenient to maintain with eliminated pipes and data cables above the printhead



- Patented special design, no wrinkle paper
- Continuous pinch roller design to prevent uneven paper
- Brush roller combined with the new paper feeder & take-up system self-recovered paper edges during operation.

## TECHNICAL PROPERTIES

Model	G30	
Print Head	30 * EPSON i3200	
Maximum Print Width	1900mm	
Motor	Linear motor	SCAN FOR PACKING DETAILS
Ink Type	Dye Sublimation Ink, Graphic Pigment Ink	
Number of Colors	4 colors, 8 colors (Optional)	
Printing Speeds	300 x 1200 – 1 pass 1200 sqm	
	360 x 1200 – 1 pass 1000 sqm	
	720 x 1200 – 2 pass 500 sqm	
Maximum Media Load	T7 Jumbo system: max. feeding 15,000m paper roll (30g)	
RIP Software	MainTop / ErgoRIP (texprint) / Neostampa / Maintop / ONYX / Caldera	
Power Supply	Total power: 29.5 kW	
Ink Tank	Big Ink Supply system, 18.5L/tank	
Operation system	windows – 64 bit system	
Net Dimensions (LxWxH)	4550x3050x2150 mm	